

JC WELDING

FUNCTIONAL SERVICING REPORT

1028 BRUCE ROAD 3

MUNICIPALITY OF BROCKTON

APRIL 2025

COBIDE Engineering Inc
517 10th Street
Hanover, ON N4N 1R4
TEL: 519-506-5959
www.cobideeng.com

TABLE OF CONTENTS

1.	INTRODUCTION	1
1.1	Location	1
1.2	Development Proposal	1
2.	STORMWATER MANAGEMENT AND SITE DRAINAGE	3
2.1	Existing drainage Conditions	3
2.2	Proposed drainage Conditions.....	3
2.3	Stormwater Modeling.....	3
2.3.1	Pre-Development Conditions	3
2.3.2	Post Development Conditions.....	3
2.3.3	SWM Facility Characteristics	4
2.4	SWM Facility Performance	4
2.4.1	Stormwater Modelling Results	4
3.	GRADING, EROSION & SEDIMENT CONTROL	6
3.1	Construction Stage	6
4.	CONCLUSIONS	7

List of Tables

Table 7.1 – SWM Facility Geometry.....	4
Table 7.2 – SWM Facility Performance.....	4
Table 2 - Stormwater Peak Flow Summary	5

LIST OF FIGURES

Figure 1 – Regional Location Map	2
--	---

APPENDICES

Appendix A – Drawings

- 13015-SP1 – Site Plan
- 13015-SWM1 – Pre Development Catchment Areas
- 13015-SWM2 – Post Development Catchment Areas

Appendix B – SWM Parameters and Output

1. INTRODUCTION

Cobide Engineering Inc. was retained by JC Welding to complete a Stormwater Management Report in support of a lot addition to expand the outside storage area and at some point in the future to expand the building.

A copy of the proposed Site Plan has been included in **Appendix A** as Drawing 13015-SP1.

1.1 LOCATION

The proposed development, herein referred to as the Site, is located on the northeast corner of the intersection of Highway 9 and Bruce Road 3, Municipality of Brockton, County of Bruce. The civic address of the Site is 1028 Bruce Road 3. A Site Location Map is included as **Figure 1**.

1.2 DEVELOPMENT PROPOSAL


The overall proposed property area is approximately 1.02 hectares (2.52 acres) in size. The owner is proposing to use the lot addition area for outdoor storage. In the future it is proposed to expand the building within the footprint of the existing lot. The site will continue to have access from Bruce Road 3.

The Site Plan showing the proposed development configuration has been included in **Appendix A** as Drawing 13015-SP1.

The Site is located on the west of Walkerton and is currently zoned Agriculture Commercial Industrial (ACI-4) within the Municipality of Brockton's zoning.



MAP SOURCE - MTO ROAD MAP



517 - 10th STREET, Hanover, Ontario N4N 1R4
Telephone: (519) 506-5959
www.cobideeng.com

Client/Project

PROPOSED LOT ADDITION

MUNICIPALITY OF BROCKTON
COUNTY OF BRUCE
FUNCTIONAL SERVICING REPORT

Figure No.

1

Title

REGIONAL LOCATION MAP

ORIGINAL SHEET - 5 x 11
H:\Planning\13015- JC Welding Lot Addition\Drawings\Submissions\2024-08-29 First Submission\13015 - JC Welding Regional Map 2024-11-14.dwg Nov 14, 2024 - 3:35pm
COPYRIGHT © COBIDE ENGINEERING INC.

Figure 1 – Regional Location Map

2. STORMWATER MANAGEMENT AND SITE DRAINAGE

The stormwater management and site drainage for the proposed development must comply with the current standards of the Town, Conservation Authority and MECP Design Guidelines. The following provides a summary of the stormwater management and site drainage plan for the development.

The recommended stormwater strategy for the development requires the post development peak flows from the property to be less than or equal to the pre-development peak flow conditions.

2.1 EXISTING DRAINAGE CONDITIONS

The majority of the lands drain uncontrolled overland to the north. A small portion discharges overland to the south where grading doesn't allow runoff to be directed to the north around the building.

2.2 PROPOSED DRAINAGE CONDITIONS

The intent of the stormwater drainage plan for the lot addition is to maintain the catchment area exactly as they are in pre development conditions. Runoff that is discharging north will be captured in a new stormwater management pond to control runoff to pre development rates.

Since the lot addition for outdoor storage will increase the overall impervious area of the subject property, stormwater runoff will need to be over-controlled in order to reduce the peak flows to pre-development conditions or less. This will be achieved through the construction of a dry pond along the northern lot boundary. The pond will provide a controlled outlet into the existing roadside ditch. A single orifice will be utilized to control flows from the development.

2.3 STORMWATER MODELING

The stormwater modeling for the pre and post development scenarios was completed using PCSWMM for the 6-hour duration, SCS Type II Distribution, Mount Forest IDF parameters.

According to the Soils Survey of Bruce County, the local native soils are reported to be Harriston Loam which are classified as Hydrologic Soil Group BC.

The pre- and post development model parameters and SWM outputs are included in Appendix B.

2.3.1 PRE-DEVELOPMENT CONDITIONS

The modelling has been completed for the area discharging to the north only as there are no changes proposed to the south side of the site along Highway 9. A total catchment area of 0.84 ha was used to determine the pre-development peak flows for the design storm events at the northern property boundary.

The pre-development catchment area is included in Appendix A as drawing 13015-SWM1.

2.3.2 POST DEVELOPMENT CONDITIONS

The proposed development of the site will include the construction of and expanded outdoor storage area. Grading of the site will direct all post-development run-off from the site into the proposed SWM pond. The pond will be located on the north side of the site and will provide storage for all post-development flows and control the discharge rate of the site's stormwater into the existing roadside ditch.

Stormwater modelling was based on two catchment areas for post development conditions.

The total area of Catchment 201 is 0.70 ha and includes all areas that will drain to the SWM pond. The total area of Catchment 202 is 0.14 ha and includes the area that cannot be captured in the SWM pond due to grading.

The post-development catchment area is included as Appendix A as drawing 13015-SWM2.

2.3.3 SWM FACILITY CHARACTERISTICS

The stormwater management facility and outlet structure have been designed to control peak runoff rates as well as conform to MECP best practices.

In order to provide the required volumes and discharges, a dry SWM Pond will be implemented with the following characteristics.

Table 7.1 – SWM Facility Geometry

SWM FACILITY	DETAILED DESIGN
Side Slope	3:1
SWM Facility Bottom	306.50 m
Top Elevation	308.00 m
High Water Elevation	307.74 m

The outlet configuration for the SWM Facility will be as follows:

- There will be a 175mm diameter orifice on the outlet from the site to provide stormwater control for the development.
- An emergency overflow spillway located on the west side of the pond will allow stormwater to drain from the pond during storm events larger than the 100 year storm if the primary outlet becomes blocked.

2.4 SWM FACILITY PERFORMANCE

Below is a summary of the hydraulic performance of the SWM facility during the various storm events:

Table 7.2 – SWM Facility Performance

RETURN PERIOD	PEAK FLOW (l/s)	ELEVATION (m)	VOLUME (m ³)
2 Year	60	307.10	55
5 Year	68	307.30	99
25 Year	77	307.56	171
50 Year	79	307.65	203
100 Year	82	307.74	235

2.4.1 STORMWATER MODELLING RESULTS

The table below summarizes the existing pre-development peak flows as well as the post development peak flows:

Table 3 - Stormwater Peak Flow Summary

PEAK FLOW DISCHARGE SUMMARY		
RETURN PERIOD	DISCHARGE POINT #1 (L/S)	
	PRE	POST
2 Year	68	68
5 Year	105	81
25 Year	173	99
50 Year	204	106
100 Year	236	114

As seen in the above table, all storm event peak flows are less than the pre development peak flows with the exception of the 2 year storm event which is marginally higher in the post development scenario.

2.5 STORMWATER QUALITY

Stormwater quality control will be provided by an OGS unit to meet an enhanced level of water treatment. An FD GA-8 from Hydro International has been selected for this site.

3. GRADING, EROSION & SEDIMENT CONTROL

Erosion and sediment controls shall meet the requirements of the most recent version of the MECP *Stormwater Management Planning and Design Manual* at the time of construction.

3.1 CONSTRUCTION STAGE

Prior to the start of construction, appropriate sediment control facilities are to be in place. Following are details regarding erosion and sediment control that are to be implemented:

- Placement of light duty siltation fencing is required along the along the property boundary.
- Placement of temporary straw check dams within swales and any other locations where a concentrated flow of runoff may occur. All proposed drainage swales are to be seeded during construction;
- Mud mats will be placed at construction accesses to keep public roadways free from debris during the construction period.
- Re-vegetate all disturbed areas after underground and surface works have been constructed.

Prior to removal of sediment control facilities, ensure that sediment that may have accumulated has been removed.

Once the area has been stabilized, the silt fencing can be removed.

4. CONCLUSIONS

The above assessment demonstrates that the stormwater from the proposed lot addition can be adequately managed. It is therefore recommended that the proposed lot addition be approved by the Municipality of Brockton and County of Bruce.

If you have any questions regarding the above, please contact the undersigned at 519-506-5959.

Sincerely,

COBIDE Engineering Inc.




Travis Burnside, P.Eng.
Director

H:\Planning\13015- JC Welding Lot Addition\Reports\FSR\2024-11-14 JC Welding FSR 13015.docx


Appendix A

DRAWINGS




Notes

- [illegible]

Seal not valid unless signed and dated



DEVELOPMENT SITE PLAN

Client:		JC WELDING	
Design:	TLB	Scale:	1:300
Drawn:	ID	Approved:	
Checked:	SJC		
Date:	APRIL 2025		
DRAWING No.		13015-C1	
		Design Engineer	



CAUTION:
THE POSITION OF POLE LINES, CONDUITS, WATERMAINS, SEWERS AND OTHER UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT NECESSARILY SHOWN ON THE DRAWINGS. AND, WHERE SHOWN, THE ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT GUARANTEED. BEFORE STARTING WORK, THE CONTRACTOR SHALL INFORM HIMSELF OF THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES, AND SHALL ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

Notes



Benchmark Information

1	APR 24/25	FIRST SUBMISSION	ID	TLB
No.	DATE	DESCRIPTION	BY	APPD
REVISION / ISSUE				

Seal not valid unless signed and dated




Title: **JC WELDING LOT ADDITION**
COUNTY OF BRUCE
MUNICIPALITY OF BROCKTON

PRE-DEVELOPMENT SWM AREAS

Client:		JC WELDING	
Design:	TLB	Scale:	1:300
Drawn:	ID	Approved:	
Checked:	SJC		
Date:	APRIL 2025	Design Engineer	
DRAWING No.		13015-SWM1	

H:\Master Documents_CIVIL_30\Bak Files\Ac\Public_2080\413015 - JC Welding Lot Addition Base Plan 2025-04-24.dwg Apr 24, 2025 - 8:58am



CAUTION:
THE POSITION OF POLE LINES, CONDUITS, WATERMANS, SEWERS AND OTHER
UNDERGROUND AND OVERGROUND UTILITIES AND STRUCTURES IS NOT
NECESSARILY SHOWN ON THE DRAWINGS, AND, WHERE SHOWN, THE
ACCURACY OF THE POSITION OF SUCH UTILITIES AND STRUCTURES IS NOT
GUARANTEED. BEFORE STARTING WORK, THE CONTRACTOR SHALL INFORM
HIMSELF OF THE EXACT LOCATION OF ALL SUCH UTILITIES AND STRUCTURES,
AND SHALL ASSUME ALL LIABILITY FOR DAMAGE TO THEM.

Notes

SCALE 1:300

5 0 5 10 15 20 METRES

5 0 5 10 15 20 FEET

Benchmark Information

No.	DATE	DESCRIPTION	BY	APPD
1	APR 24/25	FIRST SUBMISSION	ID	TLB
REVISION / ISSUE				

Seal not valid unless signed and dated

COBIDE
ENGINEERING INC

517 - 10th STREET, Hanover, Ontario N4N 1R4
Telephone: (519) 506-5959
www.cobideeng.com

Title: **JC WELDING LOT ADDITION**
COUNTY OF BRUCE
MUNICIPALITY OF BROCKTON

POST-DEVELOPMENT SWM AREAS

Client: **JC WELDING**

Design: **TLB** Scale: **1:300**

Drawn: **ID** Approved:

Checked: **SJC**

Date: **APRIL 2025** Design Engineer

DRAWING No. **13015-SWM2**

Appendix B

SWM PARAMETERS AND OUTPUT

Table A.1 Parameter Summary Table

SWM Conditions									
Outlet Location	Model Catchment ID	Description	Area (ha)	Drainage Channel (m)	Flow Length (m)	Gradient (%)	Total Imperv. Connected (%)	Manning's 'n' (Perv.)	CN (Perv.)
	101	Pre Development Site	0.84	64	131	3.0	29.8	0.13	78.0
	201	Post Development - Majority of Site	0.70	64	109	3.0	92.9	0.30	72.0
	202	Uncontrolled Portion of Site	0.14	200	7	33.0	0.0	0.30	72.0

Table A.2 Site Soils: (as per Ontario Soil Survey Report No. 35 for Wellington County)

Soil Type
Harriston Loam

Hydologic Soil Group
BC

TABLE OF CURVE NUMBERS (CN's)								
Land Use	Hydrologic Soil Type							
	A	AB	B	BC	C	CD	D	Manning's 'n'
Meadow	50	54	58	64.5	71	74.5	78	0.4
Woodlot	50	55.3	60.5	67	73.5	76.8	80	0.4
Long Grass	55	60	65	72	79	81.5	84	0.3
Lawns	60	65.5	71	77	83	86	89	0.25
Pasture/Range	58	61.5	65	70.5	76	78.5	81	0.17
Crop	66	70	74	78	82	84	86	0.13
Fallow (bare)	77	82	86	89	91	93	94	0.05
Built-up	60	65.5	71	77	83	89	89	0.25
Streets, paved	98	98	98	98	98	98	98	0.01

continuous grass
forests
natural, not maintained
maintained
farm pasture
farm land
idle farm land (bare)
Lawns Existing

HYDROLOGIC SOIL TYPE (%)								
Catchment	Hydrologic Soil Type							
	A	AB	B	BC	C	CD	D	TOTAL
101	0	0	0	100	0	0	0	100
201	0	0	0	100	0	0	0	100
202	0	0	0	100	0	0	0	100

LAND USE (%)										
Catchment	Meadow	Woodlot	Long Grass	Lawns	Pasture Range	Crop	Fallow (Bare)	Imperv. Not Connected (Rooftops)	Imperv. Connected	Total
101	0	0	0	0	0.0	70.2	0	0.0	29.8	100
201	0	0	7.1	0	0	0	0	0.0	92.9	100
202	0	0	100	0	0	0	0	0.0	0.0	100

CURVE NUMBER (CN)											
Catchment	Meadow	Woodlot	Long Grass	Lawns	Pasture Range	Crop	Fallow (Bare)	Built-up	Imperv. Not Connected (Rooftops)	Weighted CN - Pervious	Manning's 'n'
101	65	67	72	77	70.5	78	89	77	90	78.0	0.13
201	65	67.0	72	77	71	78	89	77	90	72.0	0.30
202	65	67	72	77	70.5	78	89	77	90	72.0	0.30


Table A.3: Impervious Area Determination

Existing Conditions						
Area of Concern	Total Area (ha)	Impervious Area Connected		Impervious Area Not Connected (Rooftops)		Total (%)
		(ha)	(%)	(ha)	(%)	
101	0.84	0.25	29.8	0.00	0.0	29.8
201	0.70	0.65	92.9	0.00	0.0	92.9
202	0.14	0.00	0.0	0.00	0.0	0.0

Table A.3 - Impervious Area Determination

					Imperv. Area	Imperv %
101	0	m of	20	m wide ROW @ 45% imperv.	0.00 ha	0.0 %
	1	Impervious Area	2500	m ² @ 100% imperv.	0.25 ha	29.8 %
	0	Roof Area	220	m ² @ 100% imperv.	0.00 ha	0.0 %
					0.25 ha	
201	0	m of	10	m wide ROW @ 50% imperv.	0.00 ha	0.0 %
	1	Impervious Area	6500	m ² @ 100% imperv.	0.65 ha	92.9 %
	0	Roof Area	220	m ² @ 100% imperv.	0.00 ha	0.0 %
					0.65 ha	
202	0	m of	20	m wide ROW @ 45% imperv.	0.00 ha	0.0 %
	0	Impervious Area	1380	m ² @ 100% imperv.	0.00 ha	0.0 %
	0	Roof Area	2025	m ² @ 100% imperv.	0.00 ha	0.0 %
					0.00 ha	

JC WELDING - SWM MODEL SCHEMATIC



Legend

- Junctions
- ▲ Outfalls
- Storages
- Conduits
- Orifices
- Subcatchments

JC WELDING – SWM MODELLING – MODEL DETAILS

[TITLE]

;;Project Title/Notes

[OPTIONS]

;;Option	Value
FLOW_UNITS	LPS
INFILTRATION	CURVE_NUMBER
FLOW_ROUTING	DYNWAVE
LINK_OFFSETS	ELEVATION
MIN_SLOPE	0
ALLOW_PONDING	NO
SKIP_STEADY_STATE	NO

START_DATE	10/1/2024
START_TIME	00:00:00
REPORT_START_DATE	10/1/2024
REPORT_START_TIME	00:00:00
END_DATE	10/2/2024
END_TIME	00:00:00
SWEEP_START	1/1
SWEEP_END	12/31
DRY_DAYS	0
REPORT_STEP	00:01:00
WET_STEP	00:05:00
DRY_STEP	00:05:00
ROUTING_STEP	5
RULE_STEP	00:00:00

INERTIAL_DAMPING	PARTIAL
NORMAL_FLOW_LIMITED	BOTH
FORCE_MAIN_EQUATION	H-W
VARIABLE_STEP	0.75
LENGTHENING_STEP	0
MIN_SURFAREA	0
MAX_TRIALS	8
HEAD_TOLERANCE	0
SYS_FLOW_TOL	5
LAT_FLOW_TOL	5
MINIMUM_STEP	0.5
THREADS	8

[EVAPORATION]

;;Data Source	Parameters
---------------	------------

;;-----

CONSTANT	0.0
DRY_ONLY	NO

[RAINGAGES]

;;Name	Format	Interval	SCF	Source
--------	--------	----------	-----	--------

;;-----

SCS_Type_II_25mm	INTENSITY	0:06	1.0	TIMESERIES SCS_Type_II_25mm
SCS_Type_II_39.8mm_2yr	INTENSITY	0:06	1.0	TIMESERIES SCS_Type_II_39.8mm_2yr
SCS_Type_II_55.1mm_5yr	INTENSITY	0:06	1.0	TIMESERIES SCS_Type_II_55.1mm_5yr
SCS_Type_II_78.1mm_25yr	INTENSITY	0:06	1.0	TIMESERIES SCS_Type_II_78.1mm_25yr
SCS_Type_II_87.6mm_50yr	INTENSITY	0:06	1.0	TIMESERIES SCS_Type_II_87.6mm_50yr
SCS_Type_II_97.1mm_100yr	INTENSITY	0:06	1.0	TIMESERIES SCS_Type_II_97.1mm_100yr

[SUBCATCHMENTS]

;;Name	Rain Gage	Outlet	Area	%Imperv	Width	%Slope	CurbLen	SnowPack
--------	-----------	--------	------	---------	-------	--------	---------	----------

;;-----

201	SCS_Type_II_97.1mm_100yr	SU1	0.7	92.9	64	3	0	
202	SCS_Type_II_97.1mm_100yr	J1	0.14	0	200	33	0	
PRE-101	SCS_Type_II_97.1mm_100yr	PRE_OUTFALL	0.84	30.5	64	3	0	

[SUBAREAS]

;;Subcatchment	N-Imperv	N-Perv	S-Imperv	S-Perv	PctZero	RouteTo	PctRouted
----------------	----------	--------	----------	--------	---------	---------	-----------

;;-----

201	0.01	0.3	0.05	0.05	25	OUTLET	
202	0.01	0.3	0.05	0.05	25	OUTLET	

JC WELDING – SWM MODELLING – MODEL DETAILS

PRE-101 0.01 0.13 0.05 0.05 25 OUTLET

[INFILTRATION]

;;Subcatchment	Param1	Param2	Param3	Param4	Param5
201	72	12.7	7	0	0
202	72	12.7	7	0	0
PRE-101	78	12.7	7	0	0

[JUNCTIONS]

;;Name	Elevation	MaxDepth	InitDepth	SurDepth	Aponded
J1	305.66	1	0	0	0

[OUTFALLS]

;;Name	Elevation	Type	Stage Data	Gated	Route To
POST_OUTFALL	0	FREE		NO	
PRE_OUTFALL	0	FREE		NO	

[STORAGE]

;;Name	Elev.	MaxDepth	InitDepth	Shape	Curve Name/Params	SurDepth	Fevap	Psi
Ksat IMD								
SU1	306.25	1.75	0	TABULAR	Pond	0	0	

[CONDUITS]

;;Name	From Node	To Node	Length	Roughness	InOffset	OutOffset	InitFlow
C1	J1	POST_OUTFALL	5.393	0.024	305.66	305	0

[ORIFICES]

;;Name	From Node	To Node	Type	Offset	Qcoeff	Gated	CloseTime
OR1	SU1	J1	SIDE	306.25	0.65	NO	0

[XSECTIONS]

;;Link	Shape	Geom1	Geom2	Geom3	Geom4	Barrels	Culvert
C1	TRIANGULAR	1	6	0	0	1	
OR1	CIRCULAR	0.175	0	0	0		

[LOSSES]

;;Link	Kentry	Kexit	Kavg	Flap Gate	Seepage

[CURVES]

;;Name	Type	X-Value	Y-Value
Pond	Storage	0	0.36
Pond		0.3	0.36
Pond		0.5	84
Pond		0.75	155
Pond		1	227
Pond		1.25	305
Pond		1.5	388
Pond		1.75	480

[TIMESERIES]

;;Name	Date	Time	Value

;SCS_Type_II_25mm design storm, total rainfall = 25 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_25mm

;SCS_Type_II_39.8mm design storm, total rainfall = 39.8 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_39.8mm_2yr

JC WELDING – SWM MODELLING – MODEL DETAILS

```
;SCS_Type_II_55.1mm design storm, total rainfall = 55.1 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_55.1mm_5yr
```

```
;SCS_Type_II_78.1mm design storm, total rainfall = 78.1 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_78.1mm_25yr
```

```
;SCS_Type_II_87.6mm design storm, total rainfall = 87.6 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_87.6mm_50yr
```

```
;SCS_Type_II_97.1mm design storm, total rainfall = 97.1 mm, rain interval = 6 minutes, rain units = mm/hr.
SCS_Type_II_97.1mm_100yr
```

```
[REPORT]
;;Reporting Options
INPUT      YES
CONTROLS   NO
SUBCATCHMENTS ALL
NODES ALL
LINKS ALL
```

```
[TAGS]
```

```
[MAP]
DIMENSIONS      484022.0693      4884053.916      484230.4907      4884244.194
UNITS            Meters
```

JC WELDING – SWM MODELLING – 2 YEAR DESIGN STORM EVENT

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 6
 Number of subcatchments ... 3
 Number of nodes 4
 Number of links 2
 Number of pollutants 0
 Number of land uses 0

Raingage Summary

Name	Data Source	Data Type	Recording Interval
SCS_Type_II_25mm	SCS_Type_II_25mm	INTENSITY	6 min.
SCS_Type_II_39.8mm_2yr	SCS_Type_II_39.8mm_2yr	INTENSITY	6 min.
SCS_Type_II_55.1mm_5yr	SCS_Type_II_55.1mm_5yr	INTENSITY	6 min.
SCS_Type_II_78.1mm_25yr	SCS_Type_II_78.1mm_25yr	INTENSITY	6 min.
SCS_Type_II_87.6mm_50yr	SCS_Type_II_87.6mm_50yr	INTENSITY	6 min.
SCS_Type_II_97.1mm_100yr	SCS_Type_II_97.1mm_100yr	INTENSITY	6 min.

Subcatchment Summary

Name	Area	Width	%Imperv	%Slope	Rain Gage	Outlet
201	0.70	64.00	92.90	3.0000	SCS_Type_II_39.8mm_2yr	SU1
202	0.14	200.00	0.00	33.0000	SCS_Type_II_39.8mm_2yr	J1
PRE-101	0.84	64.00	30.50	3.0000	SCS_Type_II_39.8mm_2yr	PRE_OUTFALL

Node Summary

Name	Type	Invert Elev.	Max. Depth	Ponded Area	External Inflow
J1	JUNCTION	305.66	1.00	0.0	
POST_OUTFALL	OUTFALL	0.00	306.00	0.0	
PRE_OUTFALL	OUTFALL	0.00	0.00	0.0	
SU1	STORAGE	306.25	1.75	0.0	

Link Summary

Name	From Node	To Node	Type	Length	%Slope	Roughness
C1	J1	POST_OUTFALL	CONDUIT	5.4	12.3308	0.0240
OR1	SU1	J1	ORIFICE			

Cross Section Summary

Conduit	Shape	Full Depth	Full Area	Hyd. Rad.	Max. Width	No. of Barrels	Full Flow
C1	TRIANGULAR	1.00	3.00	0.47	6.00	1	26698.83

JC WELDING – SWM MODELLING – 2 YEAR DESIGN STORM EVENT

Analysis Options

Flow Units LPS

Process Models:

Rainfall/Runoff YES

RDII NO

Snowmelt NO

Groundwater NO

Flow Routing YES

Ponding Allowed NO

Water Quality NO

Infiltration Method CURVE_NUMBER

Flow Routing Method DYNWAVE

Surcharge Method EXTRAN

Starting Date 10/01/2024 00:00:00

Ending Date 10/02/2024 00:00:00

Antecedent Dry Days 0.0

Report Time Step 00:01:00

Wet Time Step 00:05:00

Dry Time Step 00:05:00

Routing Time Step 5.00 sec

Variable Time Step YES

Maximum Trials 8

Number of Threads 1

Head Tolerance 0.001524 m

	Volume	Depth
Runoff Quantity Continuity	hectare-m	mm
*****	-----	-----
Total Precipitation	0.067	39.800
Evaporation Loss	0.000	0.000
Infiltration Loss	0.020	12.178
Surface Runoff	0.046	27.646
Final Storage	0.000	0.062
Continuity Error (%)	-0.217	

	Volume	Volume
Flow Routing Continuity	hectare-m	10^6 ltr
*****	-----	-----
Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	0.046	0.465
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000
External Outflow	0.046	0.465
Flooding Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.000	0.000
Continuity Error (%)	0.000	

Time-Step Critical Elements

Link C1 (42.56%)

Highest Flow Instability Indexes

All links are stable.

JC WELDING – SWM MODELLING – 2 YEAR DESIGN STORM EVENT

Most Frequent Nonconverging Nodes

Convergence obtained at all time steps.

Routing Time Step Summary

```

Minimum Time Step      :    1.49 sec
Average Time Step      :    3.95 sec
Maximum Time Step      :    5.00 sec
% of Time in Steady State :    0.00
Average Iterations per Step :    2.00
% of Steps Not Converging :    0.00
Time Step Frequencies :
    5.000 - 3.155 sec :    61.35 %
    3.155 - 1.991 sec :    28.73 %
    1.991 - 1.256 sec :     9.91 %
    1.256 - 0.792 sec :     0.00 %
    0.792 - 0.500 sec :     0.00 %
  
```

Subcatchment Runoff Summary

		Total	Total	Total	Total	Imperv	Perv	Total	Total
Peak	Runoff	Precip	Runon	Evap	Infil	Runoff	Runoff	Runoff	Runoff
Runoff	Coeff	mm	mm	mm	mm	mm	mm	mm	10^6 ltr
Subcatchment									
LPS									

201		39.80	0.00	0.00	2.01	37.09	0.81	37.90	0.27
136.65	0.952								
202		39.80	0.00	0.00	28.37	0.00	11.40	11.40	0.02
8.67	0.286								
PRE-101		39.80	0.00	0.00	17.95	12.17	9.64	21.81	0.18
67.47	0.548								

Node Depth Summary

		Average	Maximum	Maximum	Time of Max	Reported
Node	Type	Depth	Depth	HGL	Occurrence	Max Depth
		Meters	Meters	Meters	days hr:min	Meters
J1	JUNCTION	0.02	0.11	305.77	0 03:06	0.11
POST_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
PRE_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
SU1	STORAGE	0.08	0.85	307.10	0 03:09	0.85

Node Inflow Summary

		Maximum	Maximum	Time of Max	Lateral	Total	Flow
Node	Type	Lateral	Total	Occurrence	Inflow	Inflow	Balance
		Inflow	Inflow	days hr:min	Volume	Volume	Error
		LPS	LPS		10^6 ltr	10^6 ltr	Percent

JC WELDING – SWM MODELLING – 2 YEAR DESIGN STORM EVENT

C1 1.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 1.00 0.00 0.00

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Wed Apr 23 21:39:50 2025
Analysis ended on: Wed Apr 23 21:39:50 2025
Total elapsed time: < 1 sec

JC WELDING – SWM MODELLING – 5 YEAR DESIGN STORM EVENT

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 6

Number of subcatchments ... 3

Number of nodes 4

Number of links 2

Number of pollutants 0

Number of land uses 0

Raingage Summary

Name	Data Source	Data Type	Recording Interval
SCS_Type_II_25mm	SCS_Type_II_25mm	INTENSITY	6 min.
SCS_Type_II_39.8mm_2yr	SCS_Type_II_39.8mm_2yr	INTENSITY	6 min.
SCS_Type_II_55.1mm_5yr	SCS_Type_II_55.1mm_5yr	INTENSITY	6 min.
SCS_Type_II_78.1mm_25yr	SCS_Type_II_78.1mm_25yr	INTENSITY	6 min.
SCS_Type_II_87.6mm_50yr	SCS_Type_II_87.6mm_50yr	INTENSITY	6 min.
SCS_Type_II_97.1mm_100yr	SCS_Type_II_97.1mm_100yr	INTENSITY	6 min.

Subcatchment Summary

Name	Area	Width	%Imperv	%Slope	Rain Gage	Outlet
201	0.70	64.00	92.90	3.0000	SCS_Type_II_55.1mm_5yr	SU1
202	0.14	200.00	0.00	33.0000	SCS_Type_II_55.1mm_5yr	J1
PRE-101	0.84	64.00	30.50	3.0000	SCS_Type_II_55.1mm_5yr	PRE_OUTFALL

Node Summary

Name	Type	Invert Elev.	Max. Depth	Ponded Area	External Inflow
J1	JUNCTION	305.66	1.00	0.0	
POST_OUTFALL	OUTFALL	0.00	306.00	0.0	
PRE_OUTFALL	OUTFALL	0.00	0.00	0.0	
SU1	STORAGE	306.25	1.75	0.0	

Link Summary

Name	From Node	To Node	Type	Length	%Slope	Roughness
C1	J1	POST_OUTFALL	CONDUIT	5.4	12.3308	0.0240
OR1	SU1	J1	ORIFICE			

Cross Section Summary

Conduit	Shape	Full Depth	Full Area	Hyd. Rad.	Max. Width	No. of Barrels	Full Flow
C1	TRIANGULAR	1.00	3.00	0.47	6.00	1	26698.83

JC WELDING – SWM MODELLING – 5 YEAR DESIGN STORM EVENT

Analysis Options

Flow Units LPS
Process Models:
 Rainfall/Runoff YES
 RDII NO
 Snowmelt NO
 Groundwater NO
 Flow Routing YES
 Ponding Allowed NO
 Water Quality NO
Infiltration Method CURVE_NUMBER
Flow Routing Method DYNWAVE
Surcharge Method EXTRAN
Starting Date 10/01/2024 00:00:00
Ending Date 10/02/2024 00:00:00
Antecedent Dry Days 0.0
Report Time Step 00:01:00
Wet Time Step 00:05:00
Dry Time Step 00:05:00
Routing Time Step 5.00 sec
Variable Time Step YES
Maximum Trials 8
Number of Threads 1
Head Tolerance 0.001524 m

*****	Volume	Depth
Runoff Quantity Continuity	hectare-m	mm
*****	-----	-----
Total Precipitation	0.093	55.100
Evaporation Loss	0.000	0.000
Infiltration Loss	0.025	14.952
Surface Runoff	0.068	40.206
Final Storage	0.000	0.063
Continuity Error (%)	-0.218	

*****	Volume	Volume
Flow Routing Continuity	hectare-m	10^6 ltr
*****	-----	-----
Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	0.068	0.676
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000
External Outflow	0.068	0.676
Flooding Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.000	0.000
Continuity Error (%)	0.000	

Time-Step Critical Elements

Link C1 (45.00%)

Highest Flow Instability Indexes

All links are stable.

JC WELDING – SWM MODELLING – 5 YEAR DESIGN STORM EVENT

Most Frequent Nonconverging Nodes

Convergence obtained at all time steps.

Routing Time Step Summary

```

Minimum Time Step      :      1.43 sec
Average Time Step      :      3.80 sec
Maximum Time Step      :      5.00 sec
% of Time in Steady State :      0.00
Average Iterations per Step :      2.00
% of Steps Not Converging :      0.00
Time Step Frequencies  :
    5.000 - 3.155 sec :    58.08 %
    3.155 - 1.991 sec :    28.64 %
    1.991 - 1.256 sec :    13.27 %
    1.256 - 0.792 sec :     0.00 %
    0.792 - 0.500 sec :     0.00 %

```

Subcatchment Runoff Summary

		Total	Total	Total	Total	Imperv	Perv	Total	Total
Peak	Runoff	Precip	Runon	Evap	Infil	Runoff	Runoff	Runoff	Runoff
Runoff	Coeff	mm	mm	mm	mm	mm	mm	mm	10^6 ltr
Subcatchment									
LPS									

201		55.10	0.00	0.00	2.51	51.37	1.40	52.76	0.37
192.87	0.958								
202		55.10	0.00	0.00	35.37	0.00	19.71	19.71	0.03
15.93	0.358								
PRE-101		55.10	0.00	0.00	21.92	16.85	16.31	33.16	0.28
104.95	0.602								

Node Depth Summary

		Average	Maximum	Maximum	Time of Max	Reported
Node	Type	Depth	Depth	HGL	Occurrence	Max Depth
		Meters	Meters	Meters	days hr:min	Meters
J1	JUNCTION	0.03	0.11	305.77	0 03:06	0.11
POST_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
PRE_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
SU1	STORAGE	0.12	1.05	307.30	0 03:09	1.05

Node Inflow Summary

		Maximum	Maximum	Time of Max	Lateral	Total	Flow
Node	Type	Lateral	Total	Occurrence	Inflow	Inflow	Balance
		Inflow	Inflow	days hr:min	Volume	Volume	Error
		LPS	LPS		10^6 ltr	10^6 ltr	Percent

JC WELDING – SWM MODELLING – 5 YEAR DESIGN STORM EVENT

C1 1.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 1.00 0.00 0.00

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Fri May 9 15:22:34 2025
Analysis ended on: Fri May 9 15:22:34 2025
Total elapsed time: < 1 sec

JC WELDING – SWM MODELLING – 25 YEAR DESIGN STORM EVENT

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 6

Number of subcatchments ... 3

Number of nodes 4

Number of links 2

Number of pollutants 0

Number of land uses 0

Raingage Summary

Name	Data Source	Data Type	Recording Interval
SCS_Type_II_25mm	SCS_Type_II_25mm	INTENSITY	6 min.
SCS_Type_II_39.8mm_2yr	SCS_Type_II_39.8mm_2yr	INTENSITY	6 min.
SCS_Type_II_55.1mm_5yr	SCS_Type_II_55.1mm_5yr	INTENSITY	6 min.
SCS_Type_II_78.1mm_25yr	SCS_Type_II_78.1mm_25yr	INTENSITY	6 min.
SCS_Type_II_87.6mm_50yr	SCS_Type_II_87.6mm_50yr	INTENSITY	6 min.
SCS_Type_II_97.1mm_100yr	SCS_Type_II_97.1mm_100yr	INTENSITY	6 min.

Subcatchment Summary

Name	Area	Width	%Imperv	%Slope	Rain Gage	Outlet
201	0.70	64.00	92.90	3.0000	SCS_Type_II_78.1mm_25yr	SU1
202	0.14	200.00	0.00	33.0000	SCS_Type_II_78.1mm_25yr	J1
PRE-101	0.84	64.00	30.50	3.0000	SCS_Type_II_78.1mm_25yr	PRE_OUTFALL

Node Summary

Name	Type	Invert Elev.	Max. Depth	Ponded Area	External Inflow
J1	JUNCTION	305.66	1.00	0.0	
POST_OUTFALL	OUTFALL	0.00	306.00	0.0	
PRE_OUTFALL	OUTFALL	0.00	0.00	0.0	
SU1	STORAGE	306.25	1.75	0.0	

Link Summary

Name	From Node	To Node	Type	Length	%Slope	Roughness
C1	J1	POST_OUTFALL	CONDUIT	5.4	12.3308	0.0240
OR1	SU1	J1	ORIFICE			

Cross Section Summary

Conduit	Shape	Full Depth	Full Area	Hyd. Rad.	Max. Width	No. of Barrels	Full Flow
C1	TRIANGULAR	1.00	3.00	0.47	6.00	1	26698.83

JC WELDING – SWM MODELLING – 25 YEAR DESIGN STORM EVENT

Analysis Options

Flow Units LPS
Process Models:
 Rainfall/Runoff YES
 RDII NO
 Snowmelt NO
 Groundwater NO
 Flow Routing YES
 Ponding Allowed NO
 Water Quality NO
Infiltration Method CURVE_NUMBER
Flow Routing Method DYNWAVE
Surcharge Method EXTRAN
Starting Date 10/01/2024 00:00:00
Ending Date 10/02/2024 00:00:00
Antecedent Dry Days 0.0
Report Time Step 00:01:00
Wet Time Step 00:05:00
Dry Time Step 00:05:00
Routing Time Step 5.00 sec
Variable Time Step YES
Maximum Trials 8
Number of Threads 1
Head Tolerance 0.001524 m

*****	Volume	Depth
Runoff Quantity Continuity	hectare-m	mm
*****	-----	-----
Total Precipitation	0.131	78.100
Evaporation Loss	0.000	0.000
Infiltration Loss	0.030	18.115
Surface Runoff	0.101	60.091
Final Storage	0.000	0.063
Continuity Error (%)	-0.216	

*****	Volume	Volume
Flow Routing Continuity	hectare-m	10^6 ltr
*****	-----	-----
Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	0.101	1.011
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000
External Outflow	0.101	1.011
Flooding Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.000	0.000
Continuity Error (%)	0.000	

Time-Step Critical Elements

Link C1 (47.63%)

Highest Flow Instability Indexes

All links are stable.

JC WELDING – SWM MODELLING – 25 YEAR DESIGN STORM EVENT

Most Frequent Nonconverging Nodes

Convergence obtained at all time steps.

Routing Time Step Summary

```

Minimum Time Step      :    1.36 sec
Average Time Step      :    3.64 sec
Maximum Time Step      :    5.00 sec
% of Time in Steady State :    0.00
Average Iterations per Step :    2.00
% of Steps Not Converging :    0.00
Time Step Frequencies :
    5.000 - 3.155 sec :    55.06 %
    3.155 - 1.991 sec :    25.77 %
    1.991 - 1.256 sec :    19.17 %
    1.256 - 0.792 sec :     0.00 %
    0.792 - 0.500 sec :     0.00 %
  
```

Subcatchment Runoff Summary

		Total	Total	Total	Total	Imperv	Perv	Total	Total
Peak	Runoff	Precip	Runon	Evap	Infil	Runoff	Runoff	Runoff	Runoff
Runoff	Coeff	mm	mm	mm	mm	mm	mm	mm	10^6 ltr
Subcatchment									
LPS									

201		78.10	0.00	0.00	3.10	72.81	2.45	75.26	0.53
278.36	0.964								
202		78.10	0.00	0.00	43.62	0.00	34.49	34.49	0.05
29.06	0.442								
PRE-101		78.10	0.00	0.00	26.38	23.87	27.84	51.71	0.43
172.54	0.662								

Node Depth Summary

		Average	Maximum	Maximum	Time of Max	Reported
Node	Type	Depth	Depth	HGL	Occurrence	Max Depth
		Meters	Meters	Meters	days hr:min	Meters
J1	JUNCTION	0.04	0.12	305.78	0 03:06	0.12
POST_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
PRE_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
SU1	STORAGE	0.19	1.31	307.56	0 03:10	1.31

Node Inflow Summary

		Maximum	Maximum	Time of Max	Lateral	Total	Flow
Node	Type	Lateral	Total	Occurrence	Inflow	Inflow	Balance
		Inflow	Inflow	days hr:min	Volume	Volume	Error
		LPS	LPS		10^6 ltr	10^6 ltr	Percent

JC WELDING – SWM MODELLING – 25 YEAR DESIGN STORM EVENT

C1 1.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 1.00 0.00 0.00

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Fri May 9 15:26:17 2025
Analysis ended on: Fri May 9 15:26:17 2025
Total elapsed time: < 1 sec

JC WELDING – SWM MODELLING – 50 YEAR DESIGN STORM EVENT

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 6
 Number of subcatchments ... 3
 Number of nodes 4
 Number of links 2
 Number of pollutants 0
 Number of land uses 0

Raingage Summary

Name	Data Source	Data Type	Recording Interval
SCS_Type_II_25mm	SCS_Type_II_25mm	INTENSITY	6 min.
SCS_Type_II_39.8mm_2yr	SCS_Type_II_39.8mm_2yr	INTENSITY	6 min.
SCS_Type_II_55.1mm_5yr	SCS_Type_II_55.1mm_5yr	INTENSITY	6 min.
SCS_Type_II_78.1mm_25yr	SCS_Type_II_78.1mm_25yr	INTENSITY	6 min.
SCS_Type_II_87.6mm_50yr	SCS_Type_II_87.6mm_50yr	INTENSITY	6 min.
SCS_Type_II_97.1mm_100yr	SCS_Type_II_97.1mm_100yr	INTENSITY	6 min.

Subcatchment Summary

Name	Area	Width	%Imperv	%Slope	Rain Gage	Outlet
201	0.70	64.00	92.90	3.0000	SCS_Type_II_87.6mm_50yr	SU1
202	0.14	200.00	0.00	33.0000	SCS_Type_II_87.6mm_50yr	J1
PRE-101	0.84	64.00	30.50	3.0000	SCS_Type_II_87.6mm_50yr	PRE_OUTFALL

Node Summary

Name	Type	Invert Elev.	Max. Depth	Ponded Area	External Inflow
J1	JUNCTION	305.66	1.00	0.0	
POST_OUTFALL	OUTFALL	0.00	306.00	0.0	
PRE_OUTFALL	OUTFALL	0.00	0.00	0.0	
SU1	STORAGE	306.25	1.75	0.0	

Link Summary

Name	From Node	To Node	Type	Length	%Slope	Roughness
C1	J1	POST_OUTFALL	CONDUIT	5.4	12.3308	0.0240
OR1	SU1	J1	ORIFICE			

Cross Section Summary

Conduit	Shape	Full Depth	Full Area	Hyd. Rad.	Max. Width	No. of Barrels	Full Flow
C1	TRIANGULAR	1.00	3.00	0.47	6.00	1	26698.83

JC WELDING – SWM MODELLING – 50 YEAR DESIGN STORM EVENT

Analysis Options

Flow Units LPS
Process Models:
 Rainfall/Runoff YES
 RDII NO
 Snowmelt NO
 Groundwater NO
 Flow Routing YES
 Ponding Allowed NO
 Water Quality NO
Infiltration Method CURVE_NUMBER
Flow Routing Method DYNWAVE
Surcharge Method EXTRAN
Starting Date 10/01/2024 00:00:00
Ending Date 10/02/2024 00:00:00
Antecedent Dry Days 0.0
Report Time Step 00:01:00
Wet Time Step 00:05:00
Dry Time Step 00:05:00
Routing Time Step 5.00 sec
Variable Time Step YES
Maximum Trials 8
Number of Threads 1
Head Tolerance 0.001524 m

*****	Volume	Depth
Runoff Quantity Continuity	hectare-m	mm
*****	-----	-----
Total Precipitation	0.147	87.600
Evaporation Loss	0.000	0.000
Infiltration Loss	0.032	19.141
Surface Runoff	0.115	68.584
Final Storage	0.000	0.063
Continuity Error (%)	-0.215	

*****	Volume	Volume
Flow Routing Continuity	hectare-m	10^6 ltr
*****	-----	-----
Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	0.115	1.153
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000
External Outflow	0.115	1.153
Flooding Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.000	0.000
Continuity Error (%)	0.000	

Time-Step Critical Elements

Link C1 (48.50%)

Highest Flow Instability Indexes

All links are stable.

JC WELDING – SWM MODELLING – 50 YEAR DESIGN STORM EVENT

Most Frequent Nonconverging Nodes

Convergence obtained at all time steps.

Routing Time Step Summary

```

Minimum Time Step      :    1.34 sec
Average Time Step      :    3.58 sec
Maximum Time Step      :    5.00 sec
% of Time in Steady State :    0.00
Average Iterations per Step :    2.00
% of Steps Not Converging :    0.00
Time Step Frequencies :
    5.000 - 3.155 sec :    54.09 %
    3.155 - 1.991 sec :    24.17 %
    1.991 - 1.256 sec :    21.74 %
    1.256 - 0.792 sec :     0.00 %
    0.792 - 0.500 sec :     0.00 %
  
```

Subcatchment Runoff Summary

		Total	Total	Total	Total	Imperv	Perv	Total	Total
Peak	Runoff	Precip	Runon	Evap	Infil	Runoff	Runoff	Runoff	Runoff
Runoff	Coeff	mm	mm	mm	mm	mm	mm	mm	10^6 ltr
Subcatchment									
LPS									

201		87.60	0.00	0.00	3.30	81.67	2.93	84.60	0.59
313.90	0.966								
202		87.60	0.00	0.00	46.43	0.00	41.19	41.19	0.06
35.03	0.470								
PRE-101		87.60	0.00	0.00	27.80	26.77	33.04	59.81	0.50
203.70	0.683								

Node Depth Summary

		Average	Maximum	Maximum	Time of Max	Reported
Node	Type	Depth	Depth	HGL	Occurrence	Max Depth
		Meters	Meters	Meters	days hr:min	Meters
J1	JUNCTION	0.04	0.13	305.79	0 03:06	0.13
POST_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
PRE_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
SU1	STORAGE	0.22	1.40	307.65	0 03:10	1.40

Node Inflow Summary

		Maximum	Maximum	Time of Max	Lateral	Total	Flow
Node	Type	Lateral	Total	Occurrence	Inflow	Inflow	Balance
		Inflow	Inflow	days hr:min	Volume	Volume	Error
		LPS	LPS		10^6 ltr	10^6 ltr	Percent

JC WELDING – SWM MODELLING – 50 YEAR DESIGN STORM EVENT

C1 1.00 0.00 0.00 0.00 0.00 0.00 0.00 1.00 0.00 0.00

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Fri May 9 16:18:36 2025
Analysis ended on: Fri May 9 16:18:36 2025
Total elapsed time: < 1 sec

JC WELDING – SWM MODELLING – 100 YEAR DESIGN STORM EVENT

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

Element Count

Number of rain gages 6

Number of subcatchments ... 3

Number of nodes 4

Number of links 2

Number of pollutants 0

Number of land uses 0

Raingage Summary

Name	Data Source	Data Type	Recording Interval
SCS_Type_II_25mm	SCS_Type_II_25mm	INTENSITY	6 min.
SCS_Type_II_39.8mm_2yr	SCS_Type_II_39.8mm_2yr	INTENSITY	6 min.
SCS_Type_II_55.1mm_5yr	SCS_Type_II_55.1mm_5yr	INTENSITY	6 min.
SCS_Type_II_78.1mm_25yr	SCS_Type_II_78.1mm_25yr	INTENSITY	6 min.
SCS_Type_II_87.6mm_50yr	SCS_Type_II_87.6mm_50yr	INTENSITY	6 min.
SCS_Type_II_97.1mm_100yr	SCS_Type_II_97.1mm_100yr	INTENSITY	6 min.

Subcatchment Summary

Name	Area	Width	%Imperv	%Slope	Rain Gage	Outlet
201	0.70	64.00	92.90	3.0000	SCS_Type_II_97.1mm_100yr	SU1
202	0.14	200.00	0.00	33.0000	SCS_Type_II_97.1mm_100yr	J1
PRE-101	0.84	64.00	30.50	3.0000	SCS_Type_II_97.1mm_100yr	PRE_OUTFALL

Node Summary

Name	Type	Invert Elev.	Max. Depth	Ponded Area	External Inflow
J1	JUNCTION	305.66	1.00	0.0	
POST_OUTFALL	OUTFALL	0.00	306.00	0.0	
PRE_OUTFALL	OUTFALL	0.00	0.00	0.0	
SU1	STORAGE	306.25	1.75	0.0	

Link Summary

Name	From Node	To Node	Type	Length	%Slope	Roughness
C1	J1	POST_OUTFALL	CONDUIT	5.4	12.3308	0.0240
OR1	SU1	J1	ORIFICE			

Cross Section Summary

Conduit	Shape	Full Depth	Full Area	Hyd. Rad.	Max. Width	No. of Barrels	Full Flow
C1	TRIANGULAR	1.00	3.00	0.47	6.00	1	26698.83

JC WELDING – SWM MODELLING – 100 YEAR DESIGN STORM EVENT

Analysis Options

Flow Units LPS
Process Models:
 Rainfall/Runoff YES
 RDII NO
 Snowmelt NO
 Groundwater NO
 Flow Routing YES
 Ponding Allowed NO
 Water Quality NO
Infiltration Method CURVE_NUMBER
Flow Routing Method DYNWAVE
Surcharge Method EXTRAN
Starting Date 10/01/2024 00:00:00
Ending Date 10/02/2024 00:00:00
Antecedent Dry Days 0.0
Report Time Step 00:01:00
Wet Time Step 00:05:00
Dry Time Step 00:05:00
Routing Time Step 5.00 sec
Variable Time Step YES
Maximum Trials 8
Number of Threads 1
Head Tolerance 0.001524 m

*****	Volume	Depth
Runoff Quantity Continuity	hectare-m	mm
*****	-----	-----
Total Precipitation	0.163	97.100
Evaporation Loss	0.000	0.000
Infiltration Loss	0.034	20.078
Surface Runoff	0.130	77.167
Final Storage	0.000	0.063
Continuity Error (%)	-0.214	

*****	Volume	Volume
Flow Routing Continuity	hectare-m	10^6 ltr
*****	-----	-----
Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	0.130	1.298
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000
External Outflow	0.130	1.298
Flooding Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.000	0.000
Continuity Error (%)	0.003	

Time-Step Critical Elements

Link C1 (49.29%)

Highest Flow Instability Indexes

All links are stable.

JC WELDING – SWM MODELLING – 100 YEAR DESIGN STORM EVENT

Most Frequent Nonconverging Nodes

Convergence obtained at all time steps.

Routing Time Step Summary

```

Minimum Time Step      :    1.32 sec
Average Time Step      :    3.53 sec
Maximum Time Step      :    5.00 sec
% of Time in Steady State :    0.00
Average Iterations per Step :    2.00
% of Steps Not Converging :    0.00
Time Step Frequencies :
    5.000 - 3.155 sec :    53.22 %
    3.155 - 1.991 sec :    22.66 %
    1.991 - 1.256 sec :    24.13 %
    1.256 - 0.792 sec :     0.00 %
    0.792 - 0.500 sec :     0.00 %

```

Subcatchment Runoff Summary

		Total	Total	Total	Total	Imperv	Perv	Total	Total
Peak	Runoff	Precip	Runon	Evap	Infil	Runoff	Runoff	Runoff	Runoff
Runoff	Coeff	mm	mm	mm	mm	mm	mm	mm	10^6 ltr
Subcatchment									
LPS									

201		97.10	0.00	0.00	3.48	90.53	3.42	93.95	0.66
349.54	0.968								
202		97.10	0.00	0.00	48.97	0.00	48.16	48.16	0.07
41.25	0.496								
PRE-101		97.10	0.00	0.00	29.10	29.67	38.35	68.02	0.57
236.42	0.700								

Node Depth Summary

		Average	Maximum	Maximum	Time of Max	Reported
Node	Type	Depth	Depth	HGL	Occurrence	Max Depth
		Meters	Meters	Meters	days hr:min	Meters
J1	JUNCTION	0.04	0.13	305.79	0 03:00	0.13
POST_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
PRE_OUTFALL	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
SU1	STORAGE	0.25	1.49	307.74	0 03:10	1.49

Node Inflow Summary

		Maximum	Maximum	Time of Max	Lateral	Total	Flow
Node	Type	Lateral	Total	Occurrence	Inflow	Inflow	Balance
		Inflow	Inflow	days hr:min	Volume	Volume	Error
		LPS	LPS		10^6 ltr	10^6 ltr	Percent

JC WELDING – SWM MODELLING – 100 YEAR DESIGN STORM EVENT

C1 1.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 1.00 0.00 0.00

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Fri May 9 16:26:52 2025
Analysis ended on: Fri May 9 16:26:53 2025
Total elapsed time: 00:00:01

Hydro First Defense® - HC

Water Quality Flow Rate Worksheet

Rev. 9.6



Project Name: **JC Welding**

Report Date: **3-28-2025**

Paste

Street:

City: **Walkerton**

Province: **ON**

Country:

Designer: **TLB**

email:

Treatment Parameters:

Structure ID:
TSS Goal: **80 % Removal**
TSS Particle Size: **Fine**
Water Quality Flow: **53 L/s**
Peak Storm Flow: **96 L/s**
Peak Storm Return: **100 yrs**

RESULTS SUMMARY

Model	TSS
FD-3HC	60.0%
FD-4HC	70.4%
FD-5HC	75.7%
FD-6HC	78.9%
FD-8HC	82.0%

Performance Statement:

The Hydro International stormwater treatment system, model FD-8HC, achieves the water quality objective of 82.0% TSS using Fine particle size distribution, providing continuous treatment positive removal for the water quality flow of 53 L/s.

Model Specification:


Selected Model: **FD-8HC**
Diameter: **2400 mm**
Design WQ Flow: **53.00 L/s**
Peak Flow Capacity: **1416.00 L/s**
Sediment Storage: **2.14 m³**
Oil Storage: **4240.00 L**

Installation Configuration:

Placement: **Online**
Outlet Pipe Size: **300 mm** OK
Inlet Pipe 1 Size: **300 mm** OK
Inlet Pipe 2 Size: **mm** OK
Inlet Pipe 3 Size: **mm** OK

Rim Level: **308.000 m** **Calc Invs.**
Outlet Pipe Invert: **306.150 m** OK
Invert Pipe 1: **306.150 m** OK
Invert Pipe 2: **m** Inlet below outlet will reduce treatment capacity
Invert Pipe 3: **m** Inlet below outlet will reduce treatment capacity

Designer Notes:

**FD-8HC Specification**

1	Vortex Chamber Diameter	2400 mm
2	Inlet Pipe Diameter	300 mm
3	Oil Storage Capacity	4240 L
4	Min. Provided Sediment Storage Capacity	2.14 m ³
5	Outlet Pipe Diameter	300 mm
6	Rim to Invert	1850 mm
7	Invert to Sump	2200 mm
Total Depth		4050 mm

All drawing elevations are metres.

Designer Notes:
